

**Table 2.2 Access Management Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Left Turn Restrictions; Curb Cut and Driveway Restrictions</b>						
Turning vehicles can impede traffic flow and are more likely to be involved in crashes.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency on arterials</li> <li>▪ Improve mobility on facility</li> <li>▪ Improve travel times and reduced delay for through traffic</li> <li>▪ Fewer incidents</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Implementation and maintenance costs vary; range from new signage and striping to more costly permanent median barriers and curbs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ Localized Analysis</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Turn Lanes and New or Relocated Driveways and Exit Ramps</b>						
In some situations, increasing or modifying access to a property can be more beneficial than reducing access.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency</li> <li>▪ Improve mobility and safety on facility</li> <li>▪ Improve travel times and reduced delay for all traffic</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Additional right-of-way costs, design, construction, and maintenance costs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ Localized Analysis</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Interchange Modification</b>						
Conversion of a full cloverleaf interchange to a partial cloverleaf, for example, reduces weaving sections on a freeway.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency</li> <li>▪ Improve mobility on facility</li> <li>▪ Improve travel times and reduced delay for through traffic</li> <li>▪ Fewer incidents due to fewer conflict points</li> </ul>	<p><b>\$\$</b></p> <p>Design and construction costs.</p>	<p><u>Short-to Medium-Term: 1 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ IDAS</li> <li>▪ Regional Travel Model</li> <li>▪ Interchange Management System</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Minimum Intersection / Interchange Spacing</b>						
Reduces number of conflict points and merging areas, which in turn reduces incidents and delays.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency</li> <li>▪ Improve mobility on facility</li> <li>▪ Improve travel times and reduced delay for through traffic</li> <li>▪ Fewer incidents</li> </ul>	<p><b>\$</b></p> <p>Part of design costs for new facilities and reconstruction projects.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ Localized Analysis</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Frontage Roads and Collector-Distributor Roads</b>						
Frontage roads can be used to direct local traffic to major intersections on both super arterials and freeways. Collector-distributor roads are used to separate exiting, merging, and weaving traffic from through traffic at closely spaced interchanges.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency</li> <li>▪ Improve mobility on facility</li> <li>▪ Improve travel times and reduced delay for through traffic</li> <li>▪ Fewer incidents due to fewer conflict points</li> </ul>	<p><b>\$\$\$</b></p> <p>Additional rights-of-way costs; design, construction, and maintenance costs.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ IDAS</li> <li>▪ Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Roadway Restrictions</b>						
Closes access during rush hours (AM and PM peak hours) and aids in the increase of safety levels through the prevention of crashes at problem intersections. This measure may be effective along mainline segments of a highway, which operate at poor service levels.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency on arterials</li> <li>▪ Improve mobility on facility</li> <li>▪ Improve travel times and decrease delay for through traffic</li> <li>▪ Fewer incidents</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Additional right-of-way costs, design, construction, and maintenance costs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ Localized Analysis</li> <li>▪ Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Access Control to Available Development Sites</b>						
Coordination of access points to available development sites allows for less interference in traffic flow during construction and/or operation of new developments.	<ul style="list-style-type: none"> <li>▪ Increase capacity, efficiency on arterials</li> <li>▪ Improve mobility on facility</li> <li>▪ Improve travel times and decrease delay for through traffic</li> <li>▪ Fewer incidents</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Additional right-of-way costs, design, construction, and maintenance costs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>▪ Localized Analysis</li> <li>▪ Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>

Intersection Turn Lanes						
<p>Additional left-turn or tight-turn lanes that separate turning vehicles from through-traffic.</p>	<ul style="list-style-type: none"> <li>Greater number of vehicles can pass through the intersection in given amount of time, resulting in a lower level of travel delays and stopped time</li> <li>Can reduce the likelihood of rear-end crashes</li> </ul>	<p><b>\$ - \$\$</b> Depends on right-of-way needs.</p>	<p><u>Medium-Term: 5 to 10 Years</u> Agencies must be sure to plan for possible time needed to obtain right-of-way.</p>	<ul style="list-style-type: none"> <li>Localized Analysis</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>
Roundabout Intersections						
<p>An intersection modification that does not use traffic signal or stop sign controls. Provides continuous movement via entrance and exit lanes to/from a typically circular distribution roadway.</p>	<ul style="list-style-type: none"> <li>Greater capacity than traditional 3- or 4-way intersections in many situations</li> <li>Fewer crashes over time</li> <li>Lower air pollutant emissions due to fewer stopped vehicles</li> </ul>	<p><b>\$\$</b> Cost affected by the amount of right-of-way needed.</p>	<p><u>Medium-Term: 5 to 10 Years</u> Completion time for a replacement roundabout is related to the amount of planning and public outreach time needed and the right-of-way acquisition process.</p>	<ul style="list-style-type: none"> <li>Localized Analysis</li> </ul>	<ul style="list-style-type: none"> <li>Access Management (for the approach roadways and adjacent properties should be done)</li> <li>Operation and Management</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>
New Grade-Separated Intersections						
<p>An overpass or underpass for one roadway to avoid intersecting with a cross street.</p>	<ul style="list-style-type: none"> <li>Increase capacity, efficiency on arterials</li> <li>Improve mobility on facility</li> <li>Improve travel times and decrease delay for through traffic</li> <li>Fewer incidents</li> </ul>	<p><b>\$\$\$</b> Cost depends on the amount of right-of-way needed and the scale of construction impediments.</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u> Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Localized Analysis</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>

**Table 2.3 Active Transportation**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>New Pedestrian and Bicycle Facilities</b>						
<p>Enhancing the visibility of bicycle and pedestrian facilities increases actual and perceived safety. In many cases, bike lanes can be added to existing roadways through restriping. Use of bicycling and walking is often discouraged by a fragmentary, incomplete network of sidewalks and shared use facilities.</p> <p>Constructing new facilities, such as bike lanes (conventional / separated), shared use paths, and sidewalks will encourage greater use of walking and bicycling.</p>	<ul style="list-style-type: none"> <li>Increase mobility and access</li> <li>Increase nonmotorized mode share</li> <li>Separate slow-moving bicycles from motorized vehicles</li> <li>Reduce incidents</li> <li>Increase safety</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Implementation and maintenance costs vary; range from new signage and striping to more costly permanent median barriers and curbs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>MAG</li> <li>DRCOG</li> </ul>
<b>Improved Bicycle Facilities at Transit Stations and Other Trip Destinations</b>						
<p>Bicycle racks and bike lockers at transit stations and other trip destinations increase security. Additional amenities such as locker rooms with showers at workplaces provide further incentives for using bicycles.</p>	<ul style="list-style-type: none"> <li>Increase bicycle mode share</li> <li>Reduce motorized vehicle congestion access routes</li> </ul>	<p><b>\$</b></p> <p>Capital and maintenance costs for bicycle racks and lockers, locker rooms.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Transit</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Design Guidelines for Pedestrian-Oriented Development</b>						
<p>Maximum block lengths, building setback restrictions, and streetscape enhancements are examples of design guidelines that can be codified in zoning ordinances to encourage pedestrian activity.</p>	<ul style="list-style-type: none"> <li>Increased pedestrian mode share</li> <li>Discourage motor vehicle use for short trips</li> <li>Reduce VMT</li> <li>Reduce emission</li> </ul>	<p><b>\$</b></p> <p>Capital costs largely borne by private sector; developer incentives may be necessary. Public sector may be responsible for some capital and/or maintenance costs associated with right-of-way improvements. Ordinance development and enforcement costs.</p>	<p><u>Short-Term: 1 to 10 Years</u></p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Improved Safety of Existing Bicycle and Pedestrian Facilities</b>						
<p>Maintaining lighting, signage, striping, traffic control devices, and pavement quality, and installing curb cuts, curb extensions, median refuges, and raised crosswalks can increase bicycle and pedestrian safety.</p>	<ul style="list-style-type: none"> <li>Increased nonmotorized mode share</li> <li>Reduce incidents</li> </ul>	<p><b>\$</b></p> <p>Increased monitoring and maintenance costs. Capital costs of sidewalk improvements and additional traffic control devices.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Exclusive Non-Motorized Rights-of-Way</b>						
<p>Abandoned rail rights-of-way and existing parkland can be used for medium- to long distance bike trails, improving safety and reducing travel times.</p>	<ul style="list-style-type: none"> <li>Increase mobility</li> <li>Increase nonmotorized mode share</li> <li>Reduce congestion on nearby roads</li> <li>Separate slow-moving bicycles from motorized vehicles</li> <li>Reduce incidents</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Additional rights-of-way costs; construction, engineering, and maintenance costs.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>
<b>Bike Sharing Programs</b>						
<p>Short-term bicycle rental program supported by a network of automated rental stations.</p>	<ul style="list-style-type: none"> <li>Increased nonmotorized mode share</li> <li>Discourage motor vehicle use for short trips</li> <li>Reduce VMT</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Capital and maintenance costs for bicycles and rental stations.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transit</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>

Promoting Bicycle and Pedestrian Use Through Education and Information Dissemination						
<p>Bicycle and pedestrian use can be promoted through educational programs and through distribution of maps of bicycle facility/multi-use path maps. This may be supported by the public sector, but often could be employer-based.</p>	<ul style="list-style-type: none"> <li>Increased nonmotorized mode share</li> </ul>	<p>\$</p> <p>First-year implementation costs for private-sector. Second-year costs tend to decline. Requires public agency support; requires interagency and private-sector coordination.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>EPA Commuter Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Other Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>MAG</li> </ul>
Adopting and Implementing a Complete Streets Policy						
<p>Policy that takes into account all users of streets rather than just autos, with a goal of completing the streets with adequate facilities for all users. A "Complete Street" is one designed and operated to enable safe access for all users including pedestrians, bicyclists, motorists, and transit riders of all ages and abilities.</p>	<ul style="list-style-type: none"> <li>Increase safety by improving the overall (pedestrian and bicycle) transportation system environment</li> <li>Reduce congestion</li> <li>Provide cost savings by reducing longer distance travel and increasing shorter distance travel</li> <li>Provide travel time savings to users of the system</li> <li>Increase access to and use of nonmotorized modes</li> <li>Protect natural environment through sound land use and transportation sustainability policies</li> </ul>	<p>\$</p> <p>Policy development.</p> <p>\$ - \$\$</p> <p>For implementation.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Agencies must be sure to plan for possible time needed to obtain right-of-way.</p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>

**Table 2.4 Highway Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Increasing Number of Lanes without Highway Widening</b>						
Takes advantage of "excess" width in the highway cross section used for breakdown lanes or median.	<ul style="list-style-type: none"> <li>Increase capacity</li> <li>Reduce congestion in the short-term; long-term effects on congestion depend on local conditions</li> <li>Reduce traffic and congestion on parallel roads</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Capital costs depend on extent of modifications needed; maintenance costs increase.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>IDAS</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Geometric Design Improvements</b>						
Includes widening to provide shoulders, additional turn lanes at intersections, improved sight lines, auxiliary lanes to improve merging and diverging.  Interchange modifications to decrease weaving sections on a freeway, paved shoulders, and realignment of intersecting streets. Adding turning lanes or through lanes at an intersection, realignment of intersection streets, intersection channelization, or modifying intersection geometrics to improve overall efficiency and operation.	<ul style="list-style-type: none"> <li>Increase mobility</li> <li>Reduce congestion by improving bottlenecks</li> <li>Increase traffic flow and improve safety</li> <li>Decrease incidents due to fewer conflict points</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Design, construction, operations, and maintenance costs vary by design type.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Highway</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>MAG</li> </ul>
<b>HOV Lanes</b>						
Increases corridor capacity while at the same time providing an incentive for single-occupant drivers to shift to ridesharing.  These lanes are most effective as part of a comprehensive effort to encourage HOVs, including publicity, outreach, park- and-ride lots, and rideshare matching services.	<ul style="list-style-type: none"> <li>Reduce regional VMT and trips</li> <li>Increase vehicle occupancy / reduce SOV's</li> <li>Improve travel times</li> <li>Increase transit use and improve bus travel times</li> </ul>	<p><b>\$\$ - \$\$\$</b></p> <p>Costs depend on extent of additional right-of-way, barrier separation costs, operations, and enforcement.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>IDAS</li> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Active Transportation</li> <li>BRT / Express Bus</li> <li>Congestion Pricing</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> <li>MAG</li> <li>SLC WFRC</li> </ul>
<b>Super Street Arterials</b>						
Converting existing major arterials with signalized intersections into "super streets" that feature grade-separated intersections.	<ul style="list-style-type: none"> <li>Increase capacity</li> <li>Reduce congestion in the short-term; long-term effects on congestion depend on local conditions</li> <li>Reduce traffic and congestion on parallel roads</li> </ul>	<p><b>\$\$\$</b></p> <p>Construction and engineering substantial for grad separation.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> <li>Access Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Highway Widening by Adding Lanes</b>						
Traditional adding of lanes by widening roadway surface.	<ul style="list-style-type: none"> <li>Increase capacity</li> <li>Reduce congestion in the short-term; long-term effects on congestion depend on local conditions</li> <li>Reduce traffic and congestion on parallel roads</li> </ul>	<p><b>\$\$\$</b></p> <p>Costs vary by type of highway constructed; can be more expensive in dense urban areas. Could create negative environmental and community impacts.</p>	<p><u>Long-Term: 10+ Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> <li>Access Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>MAG</li> </ul>
<b>Acceleration/Deceleration lanes</b>						
Deceleration lane provided on a freeway just before an exit off- ramp allows vehicles to reduce speed outside the through- lanes.  Acceleration lane provided as an extension of a freeway on- ramp or an arterial street turn-lane for vehicles to increase speed and merge more smoothly into the through-lane.	<ul style="list-style-type: none"> <li>Slower-moving turning or exiting vehicles are removed from through-lanes resulting in fewer delays for upstream traffic</li> <li>Accelerating vehicles are provided more distance to reach the speed of through traffic, resulting in fewer delays caused by merging and weaving vehicles</li> <li>Could greatly reduce delays (caused by braking) for upstream vehicles during peak traffic flow periods (in certain situations)</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Costs relatively low if right-of-way or bridge widening is not required.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>IDAS</li> </ul>	<ul style="list-style-type: none"> <li>Hill Climbing Lanes</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>

Hill Climbing Lanes						
Additional lanes provided for a short distance to allow slower-moving vehicles (e.g., trucks and recreational vehicles) to move to the right and allow faster-moving vehicles to pass.	<ul style="list-style-type: none"> <li>Reduce travel time for vehicles on rural highways, especially those with peak levels of recreational traffic</li> <li>Safety benefits due to fewer frustrated drivers making dangerous passing maneuvers</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Costs relatively low if right-of-way, major rock-cuts, or environmental mitigations are not required.</p>	<p><u>Short-to Medium-Term: 1 to 10 Years</u></p> <p>Shorter segments with a right-of-way needs could be done in the short-term.</p>	<ul style="list-style-type: none"> <li>Simulation Model / HCM Software</li> </ul>	<ul style="list-style-type: none"> <li>Acceleration / Deceleration Lanes</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>
Grade Separated Railroad Crossings						
Roadway underpass or overpass of a railroad line.	<ul style="list-style-type: none"> <li>Reduced travel delays at high volume locations</li> <li>Reduce vehicle-train incidents</li> </ul>	<p><b>\$\$\$</b></p> <p>Requires construction of either a bridge or tunnel.</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u></p> <p>Implementation requires significant negotiation with railroads and local communities.</p>	<ul style="list-style-type: none"> <li>Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Highway</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>
New Freeways						
Construction of new, access-controlled, high-capacity roadways in areas previously not served by freeways.	<ul style="list-style-type: none"> <li>Reduce congestion on arterial roadway network</li> <li>Reduce travel times and delay</li> </ul>	<p><b>\$\$\$</b></p> <p>Costs vary by type of highway constructed; can be more expensive in dense urban areas. Could create negative environmental and community impacts.</p>	<p><u>Long-Term: 10+ Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Operation and Management</li> </ul>	<ul style="list-style-type: none"> <li>MAG</li> </ul>
New Arterial Streets						
Construction of new, higher-capacity roads designed to carry large volumes of traffic between areas in urban settings.	<ul style="list-style-type: none"> <li>Provide connectivity</li> <li>Carry traffic from local and collectors roads to other areas</li> <li>Increase capacity</li> <li>Reduce congestion in the short-term; long-term effects on congestion depend on local conditions</li> </ul>	<p><b>\$\$ - \$\$\$</b></p> <p>Substantial construction and engineering costs; maintenance costs depend on urban region. Could create negative environmental and community impacts.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> <li>Access Management</li> <li>Transit, as appropriate</li> </ul>	<ul style="list-style-type: none"> <li>MAG</li> </ul>
New Collectors and Local Streets						
Construction of new roadway along separate right-of-way to serve newer developed or developing areas.	<ul style="list-style-type: none"> <li>Increase capacity to serve developing areas</li> <li>Reduce traffic and congestion on parallel roads due to vehicles diverted to the new road</li> <li>Increase access / connectivity to local destinations</li> </ul>	<p><b>\$\$ - \$\$\$</b></p> <p>Costs depend on right-of-way needed and the scale of construction impediments.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Access Management</li> <li>Transit, as appropriate</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>

**Table 2.5 Land Use Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Mixed-Use Development</b>						
Allows multiple land use types within a single development or district, rather than completely segregating land uses. It facilitates the reduction of trip length and increase of walking trips.	<ul style="list-style-type: none"> <li>Increase walk trips</li> <li>Decrease SOV trips</li> <li>Decrease VMT and vehicle hours of travel</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Public costs to set up and monitor appropriate ordinances. Encourage developer buy-in with economic incentives. Regional savings in reduced new infrastructure development.</p>	<p><u>Short-to Long-Term: 1 to 10+ Years</u></p> <p>Requires supporting regulations and zoning for development to begin.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Infill and Densification</b>						
Takes advantage of existing infrastructure by encouraging development on vacant or underused parcels in already developed areas; this avoids requiring new construction of infrastructure on the fringes of the urban area.	<ul style="list-style-type: none"> <li>Decrease SOV trips</li> <li>Increase transit, walk, and bicycle trips</li> <li>Decrease VMT and vehicle trips</li> <li>Air quality improvements</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Public costs to set up and monitor appropriate ordinances. Encourage developer buy-in with economic incentives. Regional savings in reduced new infrastructure development.</p>	<p><u>Short-to Long-Term: 1 to 10+ Years</u></p> <p>Requires supporting regulations and zoning for development to begin.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>SLC WFRC</li> </ul>
<b>Transit-Oriented Development</b>						
This clusters housing units and/or businesses near transit stations in walkable communities.	<ul style="list-style-type: none"> <li>Decrease SOV trips</li> <li>Increase transit trips</li> <li>Decrease VMT</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Public costs to set up and monitor appropriate ordinances. Encourage developer buy-in with economic incentives. Regional savings in reduced new infrastructure development.</p>	<p><u>Short-to Long-Term: 1 to 10+ Years</u></p> <p>Requires supporting regulations and zoning for development to begin.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Active Transportation</li> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>MAG</li> <li>SLC WFRC</li> </ul>
<b>Trip Reduction Strategies</b>						
Plans, policies, and regulations instituted to reduce the use of SOVs for commuting; often linked to air quality planning and employer based.	<ul style="list-style-type: none"> <li>Decrease SOV trips</li> <li>Increase transit trips and non-motorized mode share</li> <li>Decrease VMT</li> </ul>	<p><b>\$</b></p> <p>First-year implementation costs for private sector (per employee equipment). Second-year costs tend to decline. Requires interagency and private sector coordination.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>EPA Commuter Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>MAG</li> </ul>
<b>Transportation Management Associations</b>						
Nonprofit, member-controlled organizations that provide transportation services in a particular area, such as a commercial district, mall, medical center, or industrial park. They are generally public-private partnerships consisting primarily of area businesses with local government support.	<ul style="list-style-type: none"> <li>Decrease SOV trips</li> <li>Increase transit trips and non-motorized mode share</li> <li>Decrease VMT</li> </ul>	<p><b>\$</b></p> <p>First-year implementation costs for private sector (per employee equipment). Second-year costs tend to decline. Requires interagency and private sector coordination.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>EPA Commuter Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>MAG</li> </ul>
<b>Last-Mile Delivery/Fulfillment Centers</b>						
Last-mile delivery centers of micro-fulfillment centers (MFCs) allow inventory to be stored closer to customers. These centers speed up deliveries and can offer in-person pick-up of packages. Governments can support these centers by repurposing urban spaces for the development of MFCs.	<ul style="list-style-type: none"> <li>Reduce last-mile delivery emissions</li> <li>Decrease last-mile delivery traffic</li> </ul>	<p><b>\$</b></p> <p>Encourage developer buy-in with economic incentives. Requires interagency and private sector coordination. Costs for outreach and publicity to encourage customers to use greener methods when picking up packages from MFCs.</p>	<p><u>Short-to Medium-Term: 1 to 10 Years</u></p>		<ul style="list-style-type: none"> <li>Active Transportation</li> <li>Other Land Use</li> </ul>	

**Table 2.6 Parking Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>On-Street Parking and Standing Restrictions</b>						
Enforcement of existing regulations can substantially improve traffic flow in urban areas. Peak-period parking prohibitions can free up extra general-purpose travel lanes or special use or HOV "diamond" lanes.	<ul style="list-style-type: none"> <li>Increase peak period capacity</li> <li>Reduce travel time and congestion on arterials</li> <li>Increase HOV and bus mode shares</li> </ul>	<p>\$</p> <p>Design, construction, and maintenance costs for signage and striping. Rigid enforcement of parking restrictions.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>IDAS</li> </ul>	<ul style="list-style-type: none"> <li>Highway</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Employer/Landlord Parking Agreements</b>						
Employers can negotiate leases so that they pay only for the number of spaces used by employees. In turn, employers can pass along parking savings by purchasing transit passes or reimbursing non-driving employees with the cash equivalent of a parking space.	<ul style="list-style-type: none"> <li>Reduce work VMT</li> <li>Increase non-motorized mode shares</li> </ul>	<p>\$</p> <p>Encourage employer and landlord buy-in with economic incentives.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Preferential or Free Parking for HOVs and Parking Management</b>						
<p>Strategies include reducing the availability of free parking spaces, particularly in congested areas, or providing preferential or free parking for HOVs. This provides an incentive for workers to carpool.</p> <p>A strategy could include a downtown employee parking payroll tax (e.g., all downtown workers pay for parking, \$5/day average for users not already paying). Other strategies include dynamic pricing, higher fees on free parking lots, parking permits (see strategies above for Parking Pricing).</p>	<ul style="list-style-type: none"> <li>Reduce work VMT</li> <li>Increase vehicle occupancy / reduce SOV's</li> </ul>	<p>\$</p> <p>Costs primarily borne by the private sector; include signing, striping, and administrative costs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Depends on political factors.</p>	<ul style="list-style-type: none"> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>Oregon DOT</li> </ul>
<b>Location-Specific Parking Ordinances</b>						
Parking requirements can be adjusted for factors such as availability of transit, a mix of land uses, or pedestrian-oriented development that may reduce the need for on-site parking. This encourages transit-oriented and mixed-use development.	<ul style="list-style-type: none"> <li>Increase transit and non-motorized mode shares</li> <li>Reduce VMT</li> </ul>	<p>\$</p> <p>Encourage developer buy-in with economic incentives.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Depends on political factors.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Land Use</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Park and Ride Lots</b>						
Park-and-Ride lots provide parking in areas that are convenient to other modes of transportation, and are commonly located adjacent to train stations, bus lines, or HOV lane facilities.	<ul style="list-style-type: none"> <li>Increase transit use and ridesharing</li> <li>Reduce VMT</li> </ul>	<p>\$ - \$\$</p> <p>Land acquisition, construction and maintenance are necessary for park-and-ride lots.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Advanced Parking Systems</b>						
Helps drivers find or reserve parking using real-time information about the status of parking availability.	<ul style="list-style-type: none"> <li>Reduce congestion on local streets</li> <li>Some peak-period travel and shift to non-motorized modes</li> </ul>	<p>\$ - \$\$</p> <p>Costs vary based on system complexity.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Local and Regional Excise Taxes</b>						
A flat fee-per-space on parking spaces provided by businesses designed to discourage automobile-dependent development, encourage more efficient land use, and - to the extent the fees are passed on to parkers - encourage non-motorized and transit choices. The revenue generated by such a tax (on parking spaces, not their use) could be used for transit and other transportation investments not eligible for highway dollars.	<ul style="list-style-type: none"> <li>Generate revenue to maintain system and address transportation improvements region-wide</li> <li>Increase non-motorized mode shares</li> <li>Reduce congestion</li> </ul>	<p>\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Depends on political factors.</p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Active Transportation</li> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>



Parking Facility Management Information Signs						
<p>Signage to notify travelers of the remaining number of unoccupied parking spaces at a public (e.g., park-and-ride) or private parking lot, guiding them to available parking.</p>	<ul style="list-style-type: none"> <li>▪ Decrease travel delay and travel miles</li> <li>▪ Improve convenience of transit; if used at park-and-ride lots</li> </ul>	<p><b>\$</b> Simple parking management can cost as low as \$20,000, whereas more sophisticated programs can exceed \$250,000 (cost and implementation).</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Transit</li> <li>▪ Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ DRCOG</li> </ul>

**Table 2.7 Regulatory Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Trip Reduction Ordinance</b>						
<p>Draws commuters to use other ways to travel to work besides driving alone. Requires employers to promote commute alternatives.</p>	<ul style="list-style-type: none"> <li>▪ Improve air quality</li> <li>▪ Reduce congestion</li> <li>▪ Minimize energy consumption</li> </ul>	<p>\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Transit</li> <li>▪ Active Transportation</li> <li>▪ Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Congestion Pricing</b>						
<p>Controls peak-period use of transportation facilities by charging more for peak-period use than for off-peak. Congestion pricing fees are charged to drivers using congested roadways during specific times of the day.</p> <p>This strategy is evaluated in order to maintain a specific level of service on a given road or all roads (areawide systems) in a region. For example, an average fee of \$0.65 cents/mile could be applied to 29 percent of urban and 7 percent of rural vehicle miles traveled (VMT) to better manage travel demand and the resulting congestion for a roadway.</p>	<ul style="list-style-type: none"> <li>▪ Increase transit and non-motorized mode shares</li> <li>▪ Decrease VMT</li> </ul>	<p>\$ - \$\$</p> <p>Implementation and maintenance costs vary.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Land Use</li> <li>▪ Operations and Management</li> <li>▪ Transit</li> <li>▪ Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> <li>▪ Oregon DOT</li> </ul>
<b>Auto Restriction Zones (Pedestrian Malls)</b>						
<p>The most common form of an auto-restriction zone (pedestrian zones) in large cities is the pedestrian mall. Pedestrian malls generally consist of a storefront-lined street that is closed off to most automobile traffic.</p> <p>Emergency vehicles always have access, while delivery vehicles may be restricted to limited delivery hours or entrances on adjacent back streets. Provides commercial access for pedestrians and non-car users.</p>	<ul style="list-style-type: none"> <li>▪ Increase capacity</li> <li>▪ Decrease travel times</li> <li>▪ Increase safety</li> <li>▪ Improve bicycle and pedestrian friendly roadways</li> </ul>	<p>\$ - \$\$</p> <p>Design, construction, and maintenance costs.</p>	<p><u>Short-to Medium- Term: 1 to 10 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Truck Restrictions</b>						
<p>Aims to separate trucks from passenger vehicles and pedestrians. Prohibits trucks from traveling on certain roadways and may call for weight restrictions on certain bridges.</p>	<ul style="list-style-type: none"> <li>▪ Increase capacity</li> <li>▪ Decrease travel times</li> <li>▪ Increase safety</li> <li>▪ Improve bicycle and pedestrian friendly roadways</li> </ul>	<p>\$</p> <p>Implementation and maintenance costs vary.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>			<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Arterial Access Management</b>						
<p>Involves the application of local and state planning, and regulatory tools in efforts to preserve and/or enhance the transportation functions of roadways. Includes land use ordinances and techniques, corridor preservation, transportation improvements, and techniques in finance.</p> <p>Actual implementation of physical access management improvements are in Table 4.2 above.</p>	<ul style="list-style-type: none"> <li>▪ Increase capacity</li> <li>▪ Decrease travel times</li> <li>▪ Increase safety</li> <li>▪ Improve bicycle and pedestrian friendly roadways</li> </ul>	<p>\$</p> <p>Implementation and maintenance costs vary.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Operations and Management</li> <li>▪ Land Use</li> <li>▪ Access Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>

Carbon Pricing /Motor Fuel Tax						
<p>Carbon pricing considers an economy wide or system strategy set either as a fuel tax or as a result of a cap-and-trade system. Motor fuel taxes, currently the primary source of revenue for highways, would increase to higher levels to generate more revenue for highways. Very high levels of either carbon prices or motor fuel taxes may affect fuel efficiency or fuel types, as well as travel demand. Carbon pricing strategies, while not implemented, consider:</p> <ul style="list-style-type: none"> <li>Environmental levy on the carbon content of fuels; and</li> <li>Dedicated fuel consumption tax to support development and maintenance of new and existing transportation systems.</li> </ul> <p>State DOTs with federal (U.S. DOT, FHWA) agency support have been assessing the potential for implementing carbon pricing strategies. An example pricing strategy could include an allowance price of \$30-50 per ton in 2030, or similar carbon tax.</p>	<ul style="list-style-type: none"> <li>Generate revenue to maintain the system and to address transportation improvements region-wide</li> <li>Reduce congestion on corridors and throughout the system</li> <li>Provide incentive to use transit, bike, and/or walk</li> </ul>	<p>\$</p>	<p><u>Long-Term: 10+ Years</u></p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Emission-Based Vehicle Registration Fees						
<p>Fees are levied based on the carbon dioxide emission levels of a car while it is operating.</p>	<ul style="list-style-type: none"> <li>Generate revenue to maintain the system and to address transportation improvements region-wide</li> <li>Reduce congestion on corridors and throughout the system</li> <li>Provide incentive to use transit, bike, and/or walk</li> <li>Provide incentive to purchase and use efficient vehicles</li> </ul>	<p>\$</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Vehicle Miles Travelled (VMT) Fee						
<p>A VMT Fee is charged based on how many miles a car is driven. Odometer readings determine the exact fee charged. A city or county could modify the structure of the fee to include a carbon fee (see Carbon Pricing/Motor Fuel Tax). VMT fees can be layered to be higher or lower based on the fuel economy of cars and layered based on urban and rural usage. Specific VMT fees of 2 to 5 cents per mile have been tested.</p> <p>VMT Fees consider distance-traveled charges levied to users based on the amount a vehicle uses a road system, while Congestion Pricing/Road User fees are levied to system users during congested periods of the day.</p>	<ul style="list-style-type: none"> <li>Generate revenue to maintain the system and to address transportation improvements region-wide</li> <li>Reduce congestion on corridors and throughout the system</li> <li>Provide incentive to use transit, bike, and/or walk</li> <li>Provide incentive to purchase and use efficient vehicles</li> </ul>	<p>\$</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Traffic Impact Fee						
<p>A charge on new development to cover the full cost of the additional transportation capacity, including transit, required to serve the development. While fee strategies may vary, in most cases, only those new developments that result in an increase in vehicle trips would be charged. Traffic impact fees can be structured as a single fee for the entire region, multiple fees for individual geographic areas, or multiple fees for specific corridors.</p> <p>Traffic impact fees vary based on the expected new development impact on the transportation system and are often structured with lower fees for developments that promote mixed use development, reduce single occupant vehicle use, and encourage transit and non-motorized travel use.</p>	<ul style="list-style-type: none"> <li>Generate revenue to maintain the system and to address transportation improvements region-wide</li> <li>Provide incentive to purchase and use efficient vehicles</li> </ul>	<p>\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Operations and Management</li> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Pay-As-You-Drive (PAYD) Insurance (State Level)						
<p>PAYD insurance considers charging drivers insurance premium costs based in part on annual vehicle miles travelled. Other insurance rating factors still apply to insurance rates, so high risk drivers pay more than lower risk drivers. All drivers have the opportunity to save money (reduced insurance fees) by driving fewer miles. The state could require insurance companies to offer PAYD insurance at lower rates and require companies to offer higher rates to encourage fewer vehicle miles travelled.</p>	<ul style="list-style-type: none"> <li>Promote transit, biking, and walking</li> <li>Reduce congestion in corridors and on transportation system</li> </ul>	<p>\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p>			<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>

**Table 2.8 Transportation Demand Management (TDM) Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Alternative Work Hours</b>						
Allows workers to arrive and leave work outside of the traditional commute period. It can be on a scheduled basis or a true flex-time arrangement. Can also include a compressed work week.	<ul style="list-style-type: none"> <li>▪ Improve travel time</li> <li>▪ Reduce peak period VMT</li> <li>▪ Reduce peak period SOV trips</li> </ul>	<p>\$</p> <p>No capital costs. Agency costs for outreach and publicity. Employer costs associated with accommodating alternative work schedules.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>▪ Regional Travel Model</li> <li>▪ TDM Evaluation Model</li> </ul>	<p>Other Transportation Demand Management</p>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> <li>▪ MAG</li> </ul>
<b>Telecommuting</b>						
Involves employees to work at home or regional telecommuting center instead of going into the office. They might do this all the time, or only one or more days per week. Also include teleconferencing and videoconferencing: the live exchange of information among several persons and machines linked by telecommunications; includes telephone conferencing and videoconferencing.	<ul style="list-style-type: none"> <li>▪ Reduce SOV trips</li> <li>▪ Reduce VMT</li> <li>▪ Decrease commuting costs</li> </ul>	<p>\$</p> <p>First year implementation costs for employee equipment from private sector. Costs tend to decline in second year.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>▪ Regional Travel Model</li> <li>▪ TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>▪ Other Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> <li>▪ DRCOG</li> <li>▪ MAG</li> <li>▪ SLC WFRC</li> </ul>
<b>Ridesharing</b>						
This is typically arranged/encouraged through employers or transportation management agencies (TMA), which provides ride-matching services. Programs to promote carpooling and vanpooling, including ridematching services and policies that give ridesharing vehicles priority in traffic and parking.	<ul style="list-style-type: none"> <li>▪ Reduce work VMT</li> <li>▪ Reduce SOV trips</li> <li>▪ Decrease commuting costs</li> </ul>	<p>\$</p> <p>Administrative costs. Costs per year per free parking space provided.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>▪ Regional Travel Model</li> <li>▪ TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>▪ Active Transportation</li> <li>▪ Transit</li> <li>▪ Highway</li> <li>▪ Other Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> <li>▪ DRCOG</li> <li>▪ MAG</li> <li>▪ SLC WFRC</li> </ul>
<b>Guaranteed Ride Home Policies</b>						
Provides a guaranteed ride home at no cost to the employee in the event an employee or a member of their immediate family becomes ill or injured, requiring the employee to leave work.	<ul style="list-style-type: none"> <li>▪ Reduce work VMT</li> <li>▪ Reduce SOV trips</li> </ul>	<p>\$</p> <p>Costs vary; requires administrative support from employers.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Active Transportation</li> <li>▪ Transit</li> <li>▪ Other Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ NYMTC</li> </ul>
<b>Alternative Travel Mode Events and Assistance</b>						
A variety of events that promote, encourage and educate people about alternative travel modes (e.g., Bike to Work Day, RideSmart Thursdays and employer transportation fairs). Can include programs that provide free or low-cost transit services (e.g., EcoPass) or other incentives.	<ul style="list-style-type: none"> <li>▪ Reduce SOV trips</li> <li>▪ Decrease commuting costs</li> </ul>	<p>\$</p> <p>Costs vary; depends on the level of participation from employers and sponsors</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Active Transportation</li> <li>▪ Transit</li> <li>▪ Highway</li> <li>▪ Other Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ DRCOG</li> </ul>
<b>Public Education Campaigns</b>						
Education related to driving habits, trip chaining, idle reduction, jackrabbit starts, Clean the Air Challenges, and others.	<ul style="list-style-type: none"> <li>▪ Various, depending on campaign</li> </ul>	<p>\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p>		<ul style="list-style-type: none"> <li>▪ Highway</li> <li>▪ Other Transportation Demand Management</li> <li>▪ Transit</li> <li>▪ Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>▪ SLC WFRC</li> </ul>

Traditional Toll Roads						
<p>Payment charged for passage on roads, bridges or ferries that carry cars. Primary use as a revenue generator to help pay for building new facilities and maintaining infrastructure. Often associated with bonding for infrastructure.</p>	<ul style="list-style-type: none"> <li>Reduce SOV trips</li> <li>Reduce trips</li> <li>Generate revenue to maintain the system and to address transportation improvements region-wide</li> </ul>	<p>\$\$\$</p> <p>High capital costs for construction of new facility; lower costs if converting an existing facility. Operating and maintenance costs may partially be recovered through toll revenue.</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Non-Traditional Toll Roads						
<p>Usually these roads, or portions of roads, are referred to as "Managed Lanes" – A toll lane or lanes designed to increase freeway efficiency through a combination of operational and design actions. This may include High Occupancy Vehicle (HOV) toll (HOT) lanes that allow a limited number of low- occupancy vehicles to use the lane if a fee is paid.</p>	<ul style="list-style-type: none"> <li>Reduce SOV trips</li> <li>Increase reliability</li> <li>Shift traffic to off-peak period times</li> <li>Generate revenue to maintain the system and to address transportation improvements region-wide</li> </ul>	<p>\$\$\$</p> <p>High capital costs for construction of new facility; lower costs if converting an existing facility. Operating and maintenance costs may partially be recovered through toll revenue.</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Operations and Management</li> <li>Transit</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Car Sharing						
<p>Program in which automobile rental services are used to substitute private vehicle use and ownership. Programs are designed to be accessible to residences, affordable, follow easy check-in/out processes, and reliable.</p> <p>Peer to peer car sharing, also known as Personal Vehicle Car-Sharing (PVCS) enables private car owners to make their vehicle available on a temporary basis to a private carsharing company for rental. In return, the vehicle owner gets a substantial portion of the rental revenue from the carsharing company. When not rented, the vehicle owner can continue to use their car as before. Commercial Car Sharing, run by private firms, maintain a fleet of vehicles that are deployed regionally (neighborhoods) for rental and use.</p>	<ul style="list-style-type: none"> <li>May increase non-motorized mode share</li> <li>Provide cost savings to users</li> </ul>	<p>\$\$\$</p> <p>Costs may be privately funded. Revenues may recover costs over time.</p>	<p><u>Short-to Medium-Term: 1 to 10 Years</u></p> <p>Implementation time depends on the level of service changes and magnitude of project.</p>		<ul style="list-style-type: none"> <li>Land Use</li> <li>Transportation Demand Management</li> <li>Transit</li> <li>Active Transportation</li> </ul>	<ul style="list-style-type: none"> <li>Oregon DOT</li> </ul>
Alternative Truck Freight Delivery Hours						
<p>Urban businesses schedule freight truck delivery hours in the evening off-peak hours. This strategy reduces large truck freights from traveling through and parking in denser urban areas during peak business hours.</p>	<ul style="list-style-type: none"> <li>Reduce peak period congestion in urban areas</li> <li>Decrease fuel consumption</li> </ul>	<p>\$</p> <p>Depending on surrounding land uses potential need to mitigate noises that may bother neighbors.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>			

**Table 2.9 Transit Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Reducing Transit Fares</b>						
Encourages additional transit use, to the extent that high fares are a barrier to transit.	<ul style="list-style-type: none"> <li>Increase transit ridership</li> <li>Reduce VMT</li> <li>Reduce congestion</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Total operating costs may increase if ridership increases. Operating subsidies needed to replace lost fare revenues.</p>	<u>Short-Term: 1 to 5 Years</u>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Land Use</li> <li>Other Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Increasing Bus Route Coverage / Frequencies</b>						
<p>Provides better accessibility to transit to a greater share of the population. Increasing frequency makes transit more attractive to use.</p> <p>May require investment in new buses which would create a capital cost per passenger trip. May also include new routes or extensions to existing routes.</p>	<ul style="list-style-type: none"> <li>Increase transit ridership</li> <li>Reduce VMT</li> <li>Decrease travel time</li> <li>Improve convenience and travel reliability</li> <li>Reduce traffic congestions due to trips switching from driving to taking transit</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Likely requires new bus purchases; increased operating costs.</p>	<u>Short-Term: 1 to 5 Years</u> Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Transit</li> <li>Land Use</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> <li>MAG</li> </ul>
<b>Park-and-Ride Lots</b>						
Provides a location for individuals to park their vehicles to join carpools or access transit. Can be used in conjunction with HOV lanes and/or express bus services. They are particularly helpful for encouraging HOV use for longer distance commute trips.	<ul style="list-style-type: none"> <li>Reduce regional VMT</li> <li>Reduce SOV trips</li> <li>Increase mobility and transit efficiency</li> <li>Increase transit boardings and mode share</li> <li>Decrease congestion</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Costs for transit stations and land acquisition.</p>	<u>Medium-Term: 5 to 10 Years</u> Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TDM Evaluation Model</li> </ul>	<ul style="list-style-type: none"> <li>Active Transportation</li> <li>Other Transit</li> <li>Highway</li> </ul>	<ul style="list-style-type: none"> <li>SLC WFRC</li> </ul>
<b>Light, Heavy, and Commuter Rail</b>						
Exclusive guideways (e.g., light rail, heavy/commuter rail) and street travelways (e.g., 16th Street Mall, bus rapid transit (BRT)) devoted to increasing the person-carrying capacity within a travel corridor.	<ul style="list-style-type: none"> <li>Reduce VMT</li> <li>Reliable (and sometimes faster than driving) travel times</li> <li>Reduce SOV trips</li> <li>Increase person throughput capacity within a corridor due to people switching from SOV to transit</li> <li>Encourages efficient mixed-use or higher-density development</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Costs vary; could be high due to right-of-way acquisition, materials, and infrastructure. New systems require large upfront capital and ongoing operation costs.</p>	<u>Medium-to Long-Term: 5 to 10+ Years</u> A rail project is a major undertaking that can take 10 plus years from initial planning phases, through NEPA studies, to opening day.	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Active Transportation</li> <li>Other Transit</li> <li>Land Use</li> <li>Highway</li> <li>Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> <li>MAG</li> </ul>
<b>Employer Incentive Programs</b>						
Encourages additional transit use through transit subsidies of mass transit fares provided by employers.	<ul style="list-style-type: none"> <li>Increase transit ridership</li> <li>Decrease travel time</li> <li>Reduce VMT</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Costs for employers to offer incentives to employee benefits for transit use.</p>	<u>Short-Term: 1 to 5 Years</u>		<ul style="list-style-type: none"> <li>Other Transit</li> <li>Transportation Demand Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Electronic Payment Systems and Universal Farecards</b>						
Equipment that allows riders to electronically pay a transit fare by using credit, debit and magnetic fare cards. Interchangeable smartcard payment system (including RFID) can be used as a fare payment method for multiple transit agencies throughout the region.	<ul style="list-style-type: none"> <li>Increase transit ridership</li> <li>Decrease travel time</li> <li>Decrease operating costs</li> </ul>	<p><b>\$\$ - \$\$\$</b></p> <p>Costs to implement electronic fare collection equipment can be high; costs vary based on system design, functionality, and technology. An initial surge in the maintenance and repair of electronic fare equipment can be expected due to the need for highly trained personnel.</p>	<u>Short-Term: 1 to 5 Years</u>		<ul style="list-style-type: none"> <li>Other Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> </ul>

Realigned Transit Service Schedules and Stop Locations						
Service adjustments to better align transit service with ridership markets.	<ul style="list-style-type: none"> <li>Increase transit ridership</li> <li>Reduce VMT</li> </ul>	\$	<u>Short-Term: 1 to 5 Years</u>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Intelligent Transit Stops						
Ranges from kiosks, which show static transit schedules, to real-time information on schedules, locations of transit vehicles, arrival time of the vehicle, and alternative routes and modes.	<ul style="list-style-type: none"> <li>Reduce VMT</li> <li>Increase transit ridership</li> <li>Decrease congestion</li> </ul>	\$ - \$\$	<u>Medium-Term: 5 to 10 Years</u>	Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Other Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Transit Intersection Queue Jump Lanes and Signal Priority						
Additional travel lane at a signalized intersection that allows buses to proceed via their own "green time" before other vehicles. Done by restriping within existing road footprint or may require construction.	<ul style="list-style-type: none"> <li>Reduce bus travel delays and improve reliability</li> <li>Improved operational efficiency of transit service</li> <li>Increase transit ridership</li> <li>Safer driving conditions for all road users</li> </ul>	\$ - \$\$	<u>Short-Term: 1 to 5 Years</u>	Planning, engineering, and implementation can reasonably be completed in less than one year; longer time is needed if new lane must be constructed.	<ul style="list-style-type: none"> <li>Localized Analysis</li> <li>Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Highway</li> <li>Other Transit</li> <li>DRCOG</li> <li>NYMTC</li> </ul>
Enhanced Transit Amenities						
Includes vehicle replacement/upgrades and better shelters or stations, which furthers the benefits of increased transit use.	<ul style="list-style-type: none"> <li>Reduce VMT</li> <li>Decrease congestion</li> <li>Increase transit ridership</li> </ul>	\$ - \$\$	<u>Short-Term: 1 to 5 Years</u>	Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Other Transit</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Dedicated Rights-of-Way for Transit						
Reserved travel lanes or rights-of-way for transit operations, including use of shoulders during peak periods.	<ul style="list-style-type: none"> <li>Decrease travel time</li> <li>Increase transit ridership</li> </ul>	\$ - \$\$	<u>Medium-Term: 5 to 10 Years</u>	Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Simulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Highway</li> <li>Other Transit</li> <li>NYMTC</li> </ul>
Bus Rapid Transit (BRT)						
High-capacity, highly efficient bus service designed to compete with rail in terms of quality of service.	<ul style="list-style-type: none"> <li>Reduce VMT</li> <li>Reduce SOV trips</li> <li>Increase transit ridership and mode share</li> </ul>	\$\$ - \$\$\$	<u>Long-Term: 10+ Years</u>	Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>EPA Commuter Model</li> </ul>	<ul style="list-style-type: none"> <li>Highway</li> <li>Other Transit</li> <li>Operations and Management</li> <li>MAG</li> </ul>
Express Bus Service						
Bus service with high-speed operations, usually between two commuter points.	<ul style="list-style-type: none"> <li>Reduce VMT</li> <li>Reduce SOV trips</li> <li>Increase transit ridership and mode share</li> </ul>	\$ - \$\$	<u>Short-Term: 1 to 5 Years</u>	Includes planning, engineering, and construction.	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>EPA Commuter Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Transit</li> <li>Operations and Management</li> <li>MAG</li> </ul>
Local Circulator						
Fixed-route service within an activity area, such as a CBD or campus, designed to reduce short trips by car.	<ul style="list-style-type: none"> <li>Reduce VMT</li> <li>Reduce SOV trips</li> <li>Increase transit ridership and boardings</li> </ul>	\$ - \$\$	<u>Short-Term: 1 to 5 Years</u>	Includes planning, engineering, and construction. May require purchase of new buses.	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>EPA Commuter Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Transit</li> <li>MAG</li> </ul>

**Table 2.10 Transportation Operations and Management Strategies**

Strategies / Projects	Congestion and Mobility Benefits	Cost and Impacts	Implementation Timeframe	Analysis Method	Complementary Strategy	Other Toolbox Examples
<b>Traffic Signal Coordination and Modernization</b>						
Improves traffic flow and reduces emissions by minimizing stops on arterial streets. Enhancements to timing/coordination plans and equipment to improve traffic flow and decrease the number of vehicle stops. May include: <ul style="list-style-type: none"> <li>Modern technology that provides for real-time traffic and transit management</li> <li>Equipment that may permit immediate knowledge of malfunctions</li> <li>Responsive control that allows traffic signals to alter timing in response to immediate traffic flow conditions, rather than at predetermined times</li> <li>Transit signal priority system that can extend "green-time" a few seconds to allow buses to progress through an intersection</li> </ul>	<ul style="list-style-type: none"> <li>Improve travel times</li> <li>Reduced number of stops</li> <li>Reduce VMT</li> <li>Reduce vehicle hours travelled</li> <li>Reduce air pollution and fuel consumption</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Varied depending on required equipment. Costs include initial investment of equipment, software, communication network and connections, and O&amp;M costs per signal.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>Microsimulation Model</li> <li>TOPS-BC</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> <li>MAG</li> <li>SLC WFRC</li> </ul>
<b>Reversible Traffic Lanes</b>						
These are appropriate where traffic flow is highly directional. Can entail a variety of different types of movable barriers, signage, and signaling.	<ul style="list-style-type: none"> <li>Increase peak direction capacity</li> <li>Reduce peak travel times</li> <li>Decrease vehicle hours traveled</li> </ul>	<p><b>\$\$ - \$\$\$</b></p> <p>Costs depend on barrier separation type and operation per mile.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>Microsimulation Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
<b>Freeway Incident Detection and Management Systems</b>						
This is an effective way to alleviate non-recurring congestion. Systems typically include video monitoring, dispatch systems, and sometimes roving service patrol vehicles.	<ul style="list-style-type: none"> <li>Reduce accident delay</li> <li>Reduce travel time</li> <li>Decrease vehicle hours traveled</li> </ul>	<p><b>\$\$ - \$\$\$</b></p> <p>Annual operating and maintenance costs.</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> </ul>
<b>Ramp Metering</b>						
Allows freeways to operate at their optimal flow rates, thereby speeding travel and reducing collisions. May include bus or high-occupancy vehicle bypass lanes. May require ramp widening to avoid extensive vehicle queuing.	<ul style="list-style-type: none"> <li>Decrease travel time</li> <li>Decrease crashes related to merging and weaving</li> <li>Improve traffic flow</li> </ul>	<p><b>\$\$</b></p> <p>Costs vary; potential significant costs associated with enhancements to centralized control system. Annual operating and maintenance costs.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TOPS-BC</li> <li>Freeval</li> <li>Microsimulation</li> </ul>	<ul style="list-style-type: none"> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> <li>MAG</li> <li>NYMTC</li> </ul>
<b>Highway Information Systems</b>						
These systems provide travelers with real-time information that can be used to make trip and route choice decisions.	<ul style="list-style-type: none"> <li>Some shift from peak-period travel to off-peak</li> <li>Reduce travel times</li> <li>Reduce travel delay</li> </ul>	<p><b>\$\$</b></p> <p>Capital, operating, and maintenance costs.</p>	<p><u>Medium -Term: 5 to 10 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TOPS-BC</li> <li>User Surveys</li> </ul>	<ul style="list-style-type: none"> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>MARC</li> </ul>
<b>Advanced Traveler Information Systems</b>						
This provides an extensive amount of data to travelers, such as real time speed estimates on the web or over wireless devices, and transit vehicle schedule progress. Provides travelers with real-time information that can be used to make trip and route choice decisions. Information accessible on the web, dynamic message signs, 511 systems, Highway Advisory Radio (HAR), or handheld wireless devices.	<ul style="list-style-type: none"> <li>Some shift from peak-period travel to off-peak</li> <li>Reduce travel times</li> <li>Reduce travel delay</li> </ul>	<p><b>\$\$</b></p> <p>Capital, operating, and maintenance costs. Private sector data available for purchase.</p>	<p><u>Medium -Term: 5 to 10 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TOPS-BC</li> <li>User Surveys</li> </ul>	<ul style="list-style-type: none"> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> <li>MAG</li> </ul>
<b>Service Patrols</b>						
Service vehicles patrol heavily traveled segments and congested sections of the freeways that are prone to incidents to provide faster and anticipatory responses to traffic incidents and disabled vehicles.	<ul style="list-style-type: none"> <li>Reduce incident duration time</li> <li>Reduce full freeway capacity</li> <li>Reduce the risks of secondary crashes to motorists</li> </ul>	<p><b>\$ - \$\$</b></p> <p>Costs vary based on number of vehicles used by the patrol, number of routes that the patrol operates, and the population of the area in which the program operates.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TOPS-BC</li> </ul>	<ul style="list-style-type: none"> <li>Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>NYMTC</li> <li>DRCOG</li> </ul>



Restricting Turns at Key Intersections						
Limits turning vehicles, which can impede traffic flow and are more likely to be involved in crashes.	<ul style="list-style-type: none"> <li>Improve mobility</li> <li>Increase capacity / efficiency on arterials</li> <li>Decrease traffic delay</li> <li>Improve travel times</li> <li>Decrease incidents</li> </ul>	<p>\$</p> <p>Implementation and maintenance costs vary; range from new signage and striping to more costly permanent median barriers and curbs.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Localized Analysis</li> </ul>		<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Converting Streets to One-Way Operations						
Establishes pairs of one-way streets in place of two-way operations. Most effective in downtown or very heavily congested areas.	<ul style="list-style-type: none"> <li>Increase traffic flow</li> </ul>	<p>\$</p> <p>Conversion costs include adjustments to traffic signals, striping, signing, and parking meters.</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Includes planning, engineering, and construction.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>Microsimulation Model</li> </ul>		<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Targeted and Sustained Enforcement of Traffic Regulations						
Improves traffic flow by reducing violations that cause delays; Includes automated enforcement (e.g., red light cameras).	<ul style="list-style-type: none"> <li>Improve travel times</li> <li>Decrease the number of stops</li> </ul>	<p>\$</p> <p>Increased labor costs per officer.</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>TOPS-BC</li> <li>Microsimulation Model</li> </ul>		<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Special Events and Work Zone Management						
Includes a suite of strategies including temporary traffic control, public awareness and motorist information, and traffic operations.	<ul style="list-style-type: none"> <li>Decrease traffic delays</li> <li>Improve mobility</li> <li>Maintain access for businesses and residents</li> </ul>	<p>\$ - \$\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>TOPS-BC</li> <li>Microsimulation Model</li> </ul>		<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Road Weather Management						
Identifying weather and road surface problems and rapidly targeting responses including advisory information, control measures, and treatment strategies.	<ul style="list-style-type: none"> <li>Increase safety</li> <li>Improve mobility</li> </ul>	<p>\$ - \$\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p>	<ul style="list-style-type: none"> <li>Maintenance Decision Support System (MDSS) Software</li> </ul>		<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Traffic Surveillance and Control Systems						
Often housed within a Traffic Management Center (TMC), monitors volume and flow of traffic by a system of sensors, and further analyzes traffic conditions to flag developing problems, and implement adjustments to traffic signal timing sequences, in order to optimize traffic flow estimating traffic parameters in real-time.  Currently, the dominant technology traffic surveillance is that of magnetic loop detectors, which are buried underneath roadways and count automobiles passing over them. Video monitoring systems for traffic surveillance may provide vehicle classifications, travel times, lane changes, rapid accelerations or decelerations, and length queues at urban intersections, in addition to vehicle counts and speeds.	<ul style="list-style-type: none"> <li>Decrease travel times</li> <li>Decrease travel delay</li> <li>Some peak-period travel and mode shift</li> </ul>	<p>\$\$</p> <p>Installation of video surveillance cameras may be less expensive than magnetic loop detectors, which require disruption and digging of the road surface.</p>	<p><u>Medium-Term: 5 to 10 Years</u></p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> <li>TOPS-BC</li> </ul>		<ul style="list-style-type: none"> <li>NYMTC</li> </ul>
Electronic Toll Collection (ETC)						
Equipment that electronically collects tolls from users without requiring vehicles to stop at a toll booth.	<ul style="list-style-type: none"> <li>Fewer vehicle stops and less traveler delay at toll stations</li> <li>Cost savings due to no (or fewer) toll booth facilities or lanes</li> <li>Decrease in pollutant emissions from stop-and-go traffic at toll booths/plazas</li> </ul>	<p>\$\$ - \$\$\$</p> <p>Initial investment in electronic toll collection technology can be substantial, for overhead transponder readers, surveillance and enforcement equipment; estimated annual maintenance and operational costs for an electronic toll lane are less than \$20,000, whereas a staffed toll booth lane can cost nearly \$200,000 annually.</p>	<p><u>Short-to Medium-Term: 1 to 10 Years</u></p> <p>Physical implementation of electronic toll collection equipment can be completed in a short time period, unless additional right-of-way is needed.</p>	<ul style="list-style-type: none"> <li>Regional Travel Model</li> </ul>	<ul style="list-style-type: none"> <li>Transit</li> <li>Highway</li> </ul>	<ul style="list-style-type: none"> <li>DRCOG</li> </ul>

Cordon Area Congestion Fees						
<p>An established cordon area or zone in which vehicles are charged a fee to enter. Such a fee can be variable (by time of day) or dynamic (based on real-time congestion conditions). Should include electronic payment/collection methods using cameras or transponders.</p>	<ul style="list-style-type: none"> <li>▪ Reduce air pollution and congestion within the cordon area</li> <li>▪ Revenue for roadway maintenance, new transit, and bicycle and pedestrian facilities</li> <li>▪ Decrease congestion</li> <li>▪ Reduce VMT</li> <li>▪ Shift to non-motorized modes</li> </ul>	<p>\$\$\$</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u></p> <p>Extensive time required for political and public discussions, possible ballot measures, construction, and implementation.</p>	<ul style="list-style-type: none"> <li>▪ Regional or Subareas Travel Demand Models</li> </ul>	<ul style="list-style-type: none"> <li>▪ Regulatory</li> <li>▪ Transit</li> <li>▪ Active Transportation</li> <li>▪ Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ Oregon DOT</li> <li>▪ DRCOG</li> </ul>
Roadway Signage Improvements						
<p>Adequate or additional signage that facilitates route-finding and the decision-making ability of roadway users. Signs with clearer/larger lettering that can be read from a greater distance. Design of signs should follow the guidance of the Manual on Uniform Traffic Control Devices (MUTCD).</p>	<ul style="list-style-type: none"> <li>▪ Increase safety</li> <li>▪ Decrease travel delay, for upstream approaching vehicles</li> </ul>	<p>\$</p>	<p><u>Short-Term: 1 to 5 Years</u></p> <p>Production of signs and installation can occur shortly after site visits and design of new signing plans.</p>			<ul style="list-style-type: none"> <li>▪ DRCOG</li> </ul>
Communications Networks and Roadway Surveillance Coverage						
<p>Base infrastructure (fiber, cameras, etc.) required to support all operational activities; Communications networks that allow remote roadway surveillance and system control from a TMC and provision of data for immediate management of transportation operations and distribution of information. Communication networks are essential to get the most efficiency and capacity out of the existing transportation system.</p>	<ul style="list-style-type: none"> <li>▪ Increase capability for regional-level coordination of operations and traveler information.</li> </ul>	<p>\$\$</p> <p>Cost can be reduced when done in conjunction with a larger scale construction project.</p>	<p><u>Medium-to Long-Term: 5 to 10+ Years</u></p> <p>Large-scale regional network components require more time for planning and funding.</p>		<ul style="list-style-type: none"> <li>▪ Other Operations and Management</li> </ul>	<ul style="list-style-type: none"> <li>▪ DRCOG</li> </ul>
Transit Vehicle Travel Information						
<p>Communications infrastructure, GPS technology, vehicle detection/monitoring devices and signs/media/Internet sites for providing information to the public such as the arrival times of the next vehicles.</p>	<ul style="list-style-type: none"> <li>▪ Improve operations and management of transit service</li> <li>▪ Increase ridership</li> <li>▪ More satisfied road users due to enhanced and reliable information sources</li> </ul>	<p>\$\$</p> <p>Costs depend upon communication networks, changing technologies, and the number of fleet vehicles to be equipped.</p>	<p><u>Medium--Term: 5 to 10 Years</u></p> <p>Time required for detailed planning, design, and funding procurement.</p>		<ul style="list-style-type: none"> <li>▪ Transit</li> </ul>	<ul style="list-style-type: none"> <li>▪ DRCOG</li> </ul>